

Page 1

Changed chart(s) since Disc 03-2011

ADD = Added chart, REV = Revised chart, DEL = Deleted chart.

ACT	PROCEDURE IDENT	INDEX	REV DATE	EFF DATE
-----	-----------------	-------	----------	----------

No revision activity since Disc 03-2011

General Info

Emmen, CHE

N 47° 05.4' E 08° 18.2' Mag Var: 0.0°W

Elevation: 1398'

Military, IFR, Control Tower, No Customs

Time Zone Info: GMT+1:00 uses DST

Runway Info

Runway 04-22 8208' x 131' asphalt

Runway 04 (36.0°M) TDZE 1400'

Lights: Edge, ALS

Displaced Threshold Distance 203'

Runway 22 (216.0°M) TDZE 1390'

Lights: Edge, ALS

Displaced Threshold Distance 408'

Communications InfoEmmen Tower **120.425** MilitaryEmmen Tower **314.97** MilitaryEmmen Approach Control **140.775** MilitaryEmmen Arrival Control **148.025** MilitaryEmmen Arrival Control **143.775** MilitaryEmmen Arrival Control **119.5** MilitaryEmmen Arrival Control **360.52** MilitaryEmmen Arrival Control **340.10** MilitaryEmmen Arrival Control **281.90** MilitaryEmmen Arrival Control **244.37** MilitaryEmmen Departure Control **148.025** MilitaryEmmen Departure Control **143.775** MilitaryEmmen Departure Control **119.5** MilitaryEmmen Departure Control **360.52** MilitaryEmmen Departure Control **340.10** MilitaryEmmen Departure Control **281.90** MilitaryEmmen Departure Control **244.37** MilitaryEmmen Information **138.05** MilitaryEmmen Information **297.10** Military**Notebook Info**


LSME/EML
 EMMEN

JEPPESEN
 1 OCT 10 10-2

EMMEN, SWITZERLAND
 STAR

Apt Elev
 1398'

Alt Set: hPa Trans level: By ATC Trans alt: 7000'
 PPR: Military procedures with permission only during mil ops hours.




AGERI THREE ECHO (AGERI 3E) [AGER3E] WILLISAU FOUR ECHO (WIL 4E) ARRIVALS

1 11,200'
 2 11,400'
 within 14 NM



TRASADINGEN
 D 114.3 TRA
 N47 41.4 E008 26.2

STAR	ROUTING
AGERI 3E	Intercept TRA R-167 inbound to ME101, intercept WIL R-081 inbound to RONIX.
WIL 4E	Intercept WIL R-081 to RONIX.

LOST COMMS ▼ LOST COMMS ▼ LOST COMMS ▼ LOST COMMS ▼ LOST COMMS ▼
 Proceed via STAR to RONIX. At last
 received or acknowledged EAT or, if no
 EAT has been received or acknowledged
 at flight planned ETA, descend in the
 RONIX holding to 5500'.
 Carry out a standard instrument approach
 for RWY-in-use.
 SWW03 LS01 ▲ SWW03 LS01 ▲ SWW03 LS01 ▲ SWW03 LS01



ILS DME
 D (110.35) IEM
 N47 05.9 E008 18.8




LSME/EML
 EMMEN

1 OCT 10

10-3

EMMEN, SWITZERLAND

SID



LSME/EML
 EMMEN

JEPPESEN
 1 OCT 10 10-3A


EMMEN, SWITZERLAND

SID

*EMMEN Departure
 119.5

Apt Elev
 1398'

Trans level: By ATC Trans alt: 7000'
 1. PPR: Military procedures with permission only during mil ops hours.
 2. Turns before DER not permitted.



WIL 4L, WIL 4R
 RWYS 04, 22 DEPARTURES

1 11,200'
 2 11,400'
 within 14 NM

Initial climb clearance FL80


ROUTING

SID	RWY	ROUTING
WIL 4L	04	Intercept IEM LOC outbound, at 2300' turn LEFT, 307° track, intercept WIL R-081 inbound to WIL.
WIL 4R	22	Turn RIGHT, 232° track, at 2200' turn RIGHT, intercept WIL R-110 inbound to WIL.

RWY 04: Close-in obstacles left and right of track up to 1600' shortly after end of RWY 04.
RWY 22: Close-in obstacle left of track up to 1500' shortly after end of RWY 22.
 These SIDs require minimum climb gradients of
WIL 4L: 286' per NM (4.7%) up to 3800'.
WIL 4R: 444' per NM (7.3%) up to 2600'.

Gnd speed-KT	75	100	150	200	250	300
444' per NM	554	739	1109	1479	1848	2218
286' per NM	357	476	714	952	1190	1428

LOST COMMS
 ▲ LOST COMMS ▼ LOST COMMS ▼ LOST COMMS ▼ LOST COMMS
 Cross WIL at last assigned and acknowledged FL, then continue climb to flight planned FL.
 L501 ▲ SWWOC L501 ▲ SWWOC L501 ▲ SWWOC L501




NOT TO SCALE

LSME/EML
Apt Elev **1398'**
N47 05.4 E008 18.2

JEPPESEN
1 OCT 10 **10-9**

EMMEN, SWITZERLAND
EMMEN



ADDITIONAL RUNWAY INFORMATION

RWY				USABLE LENGTHS		TAKE-OFF	WIDTH
				Threshold	Landing Beyond Glide Slope		
04	RL	ALS	PAPI-L (angle 4.5°)	8005' 2440m			131'
22	RL	ALS	PAPI-L (angle 4.0°)	7800' 2377m	6900' 2103m		40m

CAUTION: Crash-barrier at each end of rwy.

Standard

TAKE-OFF **1**

	LVP must be in force		NIL (DAY only)
	RCLM (DAY only) or RL	RCLM (DAY only) or RL	
A			
B	250m	400m	500m
C			
D	300m		

1 Operators applying U.S. Ops Specs: CL required below 300m.

LSME/EML


JEPPESEN
 1 OCT 10 10-9A

EMMEN, SWITZERLAND


EMMEN

TAXIING PROCEDURES

RWY 04





RWY 22



LSME/EML
EMMENJEPPESEN
1 OCT 10 11-2EMMEN, SWITZERLAND
ILS Y or LOC Y Rwy 22

BRIEFING STRIP™

*EMMEN Arrival 119.5				*EMMEN Tower 120.42	
For UHF see MIL-101 listing.					
LOC IEM *110.35	Final Apch Crs 216°	GS D3.0 IEM 2720' (1330')	ILS DA(H) Refer to Minimums	Apt Elev 1398' RWY 1390'	5500' 090° 11,200' 240° 290° 040° 9400' 14,300'
MISSED APCH: Climb STRAIGHT AHEAD. At 2000' but not before D0.9 IEM past the station turn RIGHT (MAX 210 KT, MIM BANK 25°) to intercept R-110 inbound WIL VOR. Climb to 6000'. Cross D12.0 WIL at or above 4500'. At D12.0 WIL turn RIGHT (MAX 210 KT) onto 040° to intercept R-081 WIL and proceed to RONIX.					
Alt Set: hPa Rwy Elev: 50 hPa Trans level: By ATC Trans alt: 7000' 1. PPR: Mil proc with permission only during mil ops hours. 2. ILS DME reads zero at rwy 22 displ thr.					



0.5								
Gnd speed-Kts	70	90	100	120	140	160	ALS PAPI	Refer to Missed Apch above
ILS GS or LOC Descent angle 4.00°	501	644	716	859	1002	1145		
MAP at D0.5 IEM								
Standard STRAIGHT-IN LANDING RWY 22							CIRCLE-TO-LAND	
DA(H) ILS A: 2231' (841') C: 2263' (873') B: 2248' (858') D: 2278' (888') FULL/Limited ALS out							Not authorized Southeast of apt	
LOC (GS out) DA(H) 2420' (1030') ALS out							Max Kts MDA(H) VIS	
A	RVR 1500m		RVR 1500m		100	1 2420' (1022') 1500m		
B	RVR 1500m		RVR 1500m		135	1 2420' (1022') 1600m		
C	CMV 2400m		CMV 4600m	CMV 4900m	180	3 430' (2032') 2400m 2		
D	CMV 2400m		CMV 4600m	CMV 4900m	205	4 390' (2992') 3600m 2		
1 After LOC (GS out): MDA(H) 2430' (1032'). 2 After LOC (GS out): VIS 4900m.								